LOT DETAILS

Market Support - Surplus Sales | Lot 24.20 | Total Quantity (PCS): 655,990

Lot Summary

Warehouse	Los Angeles, California	**Categories**	Opto Devices
Number of Items	49	**Total Quantity**	655,990 PCS
Pallet Weight	1,102.0 lb (499.9 kg)	**Pallet Dimensions**	48.0 x 44.0 x 71.0 in (121.9 x 111.8 x 180.3 cm)
Sales Term	Complete pallet lot; sold as-is; all sales final; no returns.	**Lot**	Lot 24.20

Items

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
1	**4N37.300-QT-C**	QT	Optoelectronics	C	DIP-6	2	18,750	4N37.300	Optocouplers,Phototransistor Output,VDE0884,CTR >=100%,IF=60mA,Vceo >=30V,Viso >=5300Vrms,Vio=1500V,Vce(Sat) <=0.3V, in DIP-6 PKG.
2	**4N38-QT-C**	QT	Optoelectronics	C	DIP-6	1	9,800	4N38	Optocouplers,Phototransistor Output,CTR 20~100%,Vceo >=80V,Viso >=5300Vrms,Vce(Sat) <=1.0V, in DIP-6 PKG
3	**5082-7650-QT-C**	QT	Optoelectronics	C	S43V4	1	1,325	-	Single Digit Display, GaAsP, Red, 630nm, Red Face, typ. 840ucd(If=5mA), C.A.
4	**CNY17-3-QT-C**	QT	Optoelectronics	C	DIP-6	1	4,950	CNY17-3	Optocouplers/TR Output, CTR 100~200%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, in DIP-6
5	**CNY17F-3-QT-C**	QT	Optoelectronics	C	DIP-6	1	6,500	CNY17F-3	Optocouplers/TR Output/GaAs Input, CTR 100~200%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, No Base Connection, in DIP-6
6	**CNY17F-4-QT-C**	QT	Optoelectronics	C	DIP-6	1	700	CNY17F-4	Optocouplers/TR Output/GaAs Input, CTR 160~320%, Vceo >=70V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=10us, toff=10us, No Base Connection, in DIP-6
7	**FLV110-QT-B**	QT	Optoelectronics	B	-	2	22,250	-	5mm Round (T-1 3/4), Cut Flange, Red, Bright(GaAsP, 660nm), Color Diffused, typ. 3mcd (10ma), 60 degree Viewing Angle
8	**H11A2-QT-C**	QT	Optoelectronics	C	DIP-6	1	450	H11A2	Optocouplers/TR Output, CTR>=20%, Vceo>=30V, Vce(Sat)<=0.4V, Iceo<=50ns, Viso>=5300VAC(rms), 1 min. Typical Ton=2us, Toff=2us, in DIP-6
9	**H11AA1-QT-C**	QT	Optoelectronics	C	DIP-6	3	11,100	H11AA1	Optocouplers/TR Output/AC Input, CTR>=20%, Vceo>=30V, Vce(Sat)<=0.4V, Iceo<=50nA, Viso>=5300VAC(rms), 1 min, in DIP-6 package
10	**H11AA2-QT-C**	QT	Optoelectronics	C	DIP-6	1	7,500	H11AA2	Optocouplers/TR Output/AC Input, CTR>=10%, Vceo>=30V, Vce(Sat)<=0.4V, Iceo<=200nA, Viso>=5300VAC(rms), 1 min, in DIP-6 package
11	**H11B1-QT-C**	QT	Optoelectronics	C	DIP-6	3	20,400	H11B1	Optocouplers/Darlington Output, CTR >=500%, Vceo >=25V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6
12	**H11B2-QT-C**	QT	Optoelectronics	C	DIP-6	1	4,500	H11B2	Optocouplers/Darlington Output, CTR >=200%, Vceo >=25V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6
13	**H11D2-QT-C**	QT	Optoelectronics	C	DIP-6	2	8,000	H11D2	High Voltage Optocouplers/TR Output/GaAs Input, CTR >=20%, Vceo >=300V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
14	**H11G2-QT-C**	QT	Optoelectronics	C	DIP-6	2	17,900	H11G2	High Voltage Optocouplers/Darlington Output/GaAs Input, CTR >=1000%, Vceo >=80V, Viso >=5300Vrms, Vce(Sat) <=1.0V, in DIP-6
15	**H22A3-QT-C**	QT	Optoelectronics	C	-	1	50	-	Optical Interrupter Switches, IF=20mA, VCE=5V, On-State Collector Current 4mA, BVCEO Min. 30v, Lead Spacing Typical 0.284

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
16	**HCPL-2530-QT-C**	QT	Optoelectronics	C	DIP-8	2	18,950	HCPL-2530	Optocouplers/Dual High Speed Transistor Output/AlGaAs Input, Viso >=2500Vrms, Ift=7.0mA,Vcc=30V,Vcc out=4.5V,Vol=0.5V, Typical Tphl=1.5us,Tplh=1.5us, in DIP-8
17	**HCPL-2601-QT-C**	QT	Optoelectronics	C	DIP-8	3	28,000	HCPL-2601	Optocouplers/Very High Speed Logic Gate Output, Viso >=2500Vrms, Typical Data Rate=10Mbit/s, Output Current TTL-loads=8.0, Propogation Delay Time Tphl=0.075ns,Tplh=0.075ns, in DIP-8
18	**HCPL-2611-QT-C**	QT	Optoelectronics	C	DIP-8	1	7,650	HCPL-2611	Optocouplers/Very High Speed Logic Gate Output, Viso >=2500Vrms, Typical Data Rate=10Mbit/s, Output Current TTL-loads=8.0, Propogation Delay Time Tphl=0.075ns,Tplh=0.075ns, in DIP-8
19	**HCPL-2730-QT-C**	QT	Optoelectronics	C	DIP-8	2	11,700	HCPL-2730	Optocouplers/Dual Split Darlington Output/AlGaAs Input, Viso >=2500Vrms, Ift=1.6mA,Vcc=7.0V,Vol=0.4V, Typical Tphl=20us,Tplh=35+us, in DIP-8
20	**HLMP-1700-QT-B**	QT	Optoelectronics	B	-	2	38,000	-	3mm Round (T-1) Small Flange with Stand-Off, Red (GaAsP, 635nm), Color Diffused, typ. 2mcd (2ma), 50 degree Viewing Angle
21	**HLMP-1790-QT-B**	QT	Optoelectronics	B	-	1	4,750	-	3mm Round (T-1) Small Flange with Stand-Off, Green (GaP, 565nm), Color Diffused, typ. 2mcd (2ma), 50 degree Viewing Angle
22	**HLMP-3300-QT-B**	QT	Optoelectronics	B	-	1	5,500	-	5mm Round (T-1 3/4), Cut Flange, Red (GaAsP, 635nm), Color Diffused, typ. 10mcd (10ma), 45 degree Viewing Angle
23	**HLMP-3850A-QT-B**	QT	Optoelectronics	B	R5	3	52,250	-	5mm(T-1 3/4) Round,Cut Flange with Stopper,Yellow LED,PL=585nm,150mcd(Typ)at 20mA, 24 Degree,in Bulk Packing
24	**HLMP-4719-QT-B**	QT	Optoelectronics	B	-	1	3,500	-	5mm Round (T-1 3/4) with Stopper, Yellow(GaAsP, 585nm), Color Diffused, typ. 2mcd (2ma), 25 degree Viewing Angle
25	**HLMP-6620-QT-B**	QT	Optoelectronics	B	C0808	1	1,000	-	SMD LF Type,1.78mm Round,5V Resistor,Axial Straight,Hi-Eff Red LED,626nm,2.0mcd(Typ),90 Degree,in Bulk Pack,Non-RoHS
26	**HLMP-D150A-QT-B**	QT	Optoelectronics	B	R5	1	500	-	5mm Round (T-1 3/4) with Cut Flange, Red (GaAlAs, 660nm), Color Diffused, typ. 3mcd(1ma), 65 degree Viewing Angle
27	**HLMP-K402-QT-B**	QT	Optoelectronics	B	R3	1	1,000	-	3mm Round (T-1), Small Flange, Stand-Off, Orange 612nm, Color Diffused, typ. 6.5mcd(10ma), 90 degree Viewing Angle
28	**HLMP-K600-QT-B**	QT	Optoelectronics	B	-	1	1,250	-	3mm Round (T-1), Small Flange, Stand-Off, Green (GaP, 560nm), Color Diffused, typ. 4.5mcd (10ma), 90 degree Viewing Angle
29	**MCT2-QT-C**	QT	Optoelectronics	C	DIP-6	1	500	MCT2	Optocouplers/TR Output, CTR >=20%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
30	**MCT2.300-QT-C**	QT	Optoelectronics	C	DIP-6	3	29,600	MCT2.300	Optocouplers/TR Output-VDE0884, CTR >=20%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
31	**MCT5211-QT-C**	QT	Optoelectronics	C	DIP-6	1	10,000	MCT5211	Optocouplers/TR Output/AlGaAs Input, CTR >=150%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, in DIP-6
32	**MCT6-QT-C**	QT	Optoelectronics	C	DIP-8	7	61,000	MCT6	Multichannel Optoisolators/TR Output, CTR >60%, Vio >=2800Vrms, Vceo >70V, Vce(Sat)<0.3V, Typical ton/toff=6.0us, in DIP-8
33	**MCT9001-QT-C**	QT	Optoelectronics	C	DIP-8	2	19,700	MCT9001	Dual Phototransistor Optocoupler, CTR 50~600%, Vf=1.0V, Viso >=4000Vdc, Vce(Sat) <=0.4V, Typical ton=3.0us, toff=3.0us, in DIP-8
34	**MOC3012-QT-C**	QT	Optoelectronics	C	DIP-6	1	500	-	Optocoupler -Traic Output (120VAC), Ift<=5mA, Vdrm=250V, Idrm<=100nA, Itsm=1A@1ms, Vtm<=3V, Ih(typ)=100uA, Viso >7500VAC(pk) in DIP-6
35	**MOC3021-QT-C**	QT	Optoelectronics	C	DIP-6	3	7,200	-	Optocoupler -Traic Output (240VAC), Ift<=15mA, Vdrm=400V, Idrm<=100nA, Itsm=1A@1ms, Vtm<=3V, Ih(typ)=100uA, Viso >7500VAC(pk) in DIP-6
36	**MOC3023-QT-C**	QT	Optoelectronics	C	DIP-6	8	43,650	-	Optocoupler -Traic Output (240VAC), Ift<=5mA, Vdrm=400V, Idrm<=100nA, Itsm=1A@1ms, Vtm<=3V, Ih(typ)=100uA, Viso >7500VAC(peak) in DIP-6
37	**MV53124A-QT-B**	QT	Optoelectronics	B	3.8X6.3MM	1	14,250	-	3.8x6.3mm Rectangular Legend with Reflector, Super Yellow LED, GaAsP, 585nm, 6.0mcd (Typ.)at 20mA, Color Diffused, 100 degree Viewing Angle, in Bulk Packing

#	Part Number	Brand	Category	Package	Outline	Cartons	Quantity	Datasheet	Description
38	**MV5353-QT-B**	QT	Optoelectronics	B	R5	1	6,500	-	5mm (T-1 3/4) Round, Cut Flange, Super Yellow LED, GaAsP, 585nm, 15mcd (Typ.)at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
39	**MV5453-QT-B**	QT	Optoelectronics	B	R5	6	74,250	-	5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 20mcd(Tpy.) at 20mA, Color Diffused, 75 degree Viewing Angle, in Bulk Packing
40	**MV57164-QT-C**	QT	Optoelectronics	C	C1004	1	240	-	10 Bar Graph Display, GaAsP Red, Hi-Eff 630nm, Gray, typ. 510mcd(If=10mA),
41	**MV5752-QT-B**	QT	Optoelectronics	B	R5	1	11,500	-	5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 100mcd(Tpy.) at 20mA, Color Tinted, 28 degree Viewing Angle, in Bulk Packing
42	**MV5753-QT-B**	QT	Optoelectronics	B	R5	3	22,500	-	5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 15mcd (Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
43	**MV6353-QT-B**	QT	Optoelectronics	B	R5	1	15,250	-	5mm (T-1 3/4) Round, Cut Flange, Super Yellow LED, GaAsP, 585nm, 15mcd(Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
44	**MV64521-QT-B**	QT	Optoelectronics	B	R5	1	1,250	-	5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 100mcd(Tpy.) at 20mA, Color Tinted, 35 degree Viewing Angle, in Bulk Packing
45	**MV6700-QT-B**	QT	Optoelectronics	B	C0809	1	1,000	-	SMD,LF Type,1.78mm Round,Axial Straight, Deep Red LED,GaAsP,635nm,3.0mcd(Tpy.) at 10mA,50 Degree,in Bulk Packing, Non-RoHS
46	**MV6753-QT-B**	QT	Optoelectronics	B	R5	2	17,750	-	5mm (T-1 3/4) Round, Cut Flange, Deep Red LED, GaAsP, 635nm, 15mcd (Tpy.) at 20mA, Color Diffused, 65 degree Viewing Angle, in Bulk Packing
47	**MV8410-QT-B**	QT	Optoelectronics	B	R5	1	1,000	-	5mm (T-1 3/4) Round , Cut Flange, Green LED, GaP, 565nm, 240mcd(Tpy.) at 20mA, Water Clear, 12 degree Viewing Angle, in Bulk Packing
48	**MV9102-QT-B**	QT	Optoelectronics	B	RA	1	125	-	10mm Small flange round led, Red LED, GaAsP, 660nm, 2400mcd(Tpy.) at 20mA, Water Clear, 8 degree Viewing Angle, in Bulk Packing
49	**SL5511-QT-C**	QT	Optoelectronics	C	DIP-6	1	10,000	SL5511	Optocouplers/TR Output, CTR 25~400%, Vceo >=30V, Viso >=5300Vrms, Vce(Sat) <=0.4V, Typical ton=20us,toff=50us, in DIP-6

Terms of Sale

All sales are final. Products are sold as-is, as complete pallet lots, with no returns. Bids are based on ex-warehouse terms. The buyer is responsible for freight, pickup, export/import requirements, taxes, duties, and applicable handling or compliance costs. Availability is subject to prior sale, bid acceptance, and final confirmation by Taitron Components.